

F-PODIUM CARBON DC R, MARLIN BLUE/CARBON/RACING SILVER, 2023

obj. č: 010.23065



Specyfikacje techniczne

produkowane rozmiary S: 380mm / M: 420mm / L: 470mm / XL: 510mm	rama F-Podium 29 Stealth Air Full Carbon, XCO Optimized Zero Suspension System, 115mm, XC Forward Geometry, Carbon Monoblock upper link, BSA bottom bracket, tapered head tube, HHG internal cable routing, dedicated 1X drivetrain design, Boost 12x148mm rear axle, shock mudguard, postmount rear brake mount.
widelec Rockshox SID Ultimate RL 29, 120mm, Charger Race day, DebonAir, tapered steerer tube, Boost 15x110mm axle, 35mm tapered aluminum stanchions, offset 44mm. Settings: OneLoc, Low-speed rebound, air preload, RockShox OneLoc	stery Acros AZX-239 R1 Block Lock, ZS44/28.6 top, ZS56/40 bottom
przerzutka Sram X01 Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1	manetki Sram Trigger GX Eagle, 12s, X-Actuation 1:1
klamki hamulca Sram Level TL, Direct Link actuation, tooled reach adjust, lever pivot bushings	uchwyty Sram X1 Carbon Eagle, Boost, DUB axle, Direct mount chain ring, S size: 170mm, M/L/XL size: 175mm
support Sram DUB BSA, sealed bearings, 73mm	kierownica Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm barbare
mostek MDK, 6061 T6 Alloy, 31.8mm barbare, rise: +/-5°, length: sizes S/M: 50mm, size L: 60mm, size XL: 70mm	sztyca Onoff Pija dropper internal, diameter 31.6mm, S size: 405x95-125mm, M size 458x120-150mm, L size: 498x140-170mm, XL size: 498x140-170mm
siodełko Fizik Antares R7	piasta przednia Infinity hub, Boost 15x110mm, IS 6 bolts
tylna piasta Infinity hub, ID360 freewheel technology, Boost 12x148mm, IS 6 bolts	łańcuch Sram GX Eagle, 12s, Powerlock
kaseta Sram XG-1275, 10-50T, 12s	szprychy 24 straight-pull double butted spokes
rafki Mavic CrossMax Carbon XL R, 29 Boost 30mm internal width, hookless, tubeless ready, 24 spokes	obudowa Maxxis Rekon Race 29x2.4, EXO protection, tubeless ready, 120TPI, folding bead
zamówienie numer 010.23065	gripy Onoff Desert, 1lock-on, 135mm

amortyzator
Rockshox SID Luxe Ultimate RLR DebonAir, 185x50mm.
Settings: OneLoc, low-speed rebound, air preload. Trunnion top mount, 22.2x10mm bottom bushings

tylny hamulec
Sram Level TL, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad

korba
34T, CNC-machined alloy, X-SYNC 2

przedni hamulec
Sram Level TL, 2 piece caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pad

regulacja amortyzatora
Light compression, medium rebound, Lockout 430, 1 Token

mocowanie przerzutki
Sram UDH

Galeria

