

# SUMMUM MX, DIRTY WHITE/ORANGE, 2023

obj. č: 010.23157

Sugerowana cena

22.499 zł



## Specyfikacje techniczne

### produkowane rozmiary

S / M / L / XL

### rama

Summum 29 6061 Alloy Stealth Evo, hydroformed tubing, Zero suspension system, 200mm travel, Forward Geometry, alloy upper link with shock eyelet bearings, SuperBoost 12x157mm rear axle, 83mm BSA bottom bracket, MAX. capacity dual row Enduro bearings, HHG internal cable routing, ISCG 05. \*Optional Geometry kit

### widelec

Rockshox Boxxer Select RC 29, 200mm, DebonAir, 1-1/8" steerer tube, Boost 20x110mm axle, offset 56mm. Settings: low-speed compression, rebound, air preload

### stery

Onoff Mercurium 1.5 ZS for 1-1/8" steerer tube, 41x30.15x7x45°x45° ACB sealed bearings, geometry kit cups, external diameter 56mm

### przerzutka

Sram GX DH, 7s, medium cage, X-actuation 1:1

### przerzutka

E.13 Vario Compact Upper Slider ,Alloy backplate ,DMB (Direct mount Bashguard) Lower Slider 34-36t, ISCG 05 adjustable upper slider

### manetki

Sram trigger GX DH 7s, X-actuation 1:1

### klamki hamulca

Sram DB8, tool-free reach adjust

### uchwyty

Truvativ Descendant DH, DUB axle, Direct mount chain ring, 165mm

### support

Sram DUB BSA, sealed bearings, 83mm

### kierownica

Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore

### mostek

Onoff Krypton DH CNC Integrated FG, 25-30mm adjustable length, 31.8mm barbore, 6061 alloy, 2x6mm spacer

### sztyca

SDG Micro I-Beam SP-751 Alloy, diameter 31.6mm, length 300mm, micro-adjustment

### siodełko

SDG I-Fly 2.0 I-Beam, high-density PU foam, Cordura sides

### piasta przednia

MDK DA4371B-M20, Boost 20x110mm, IS 6 bolts

### tylna piasta

MDK DA4352B, 12x157mm, sealed bearings, IS 6 bolts

### łańcuch

Sram PC1110 11s, Powerlock

### kaseta

Sram PG 720 11-25T, 7s

### szprychy

CN stainless steel

### rafki

MDK-DP1 29, 27mm internal width, 32 holes

### obudowa

Michelin DH34 29x2.4, tubeless ready, Magi-X DH compound, double-reinforced DH shield casing, wire bead

### zamówienie numer

010.23157

### gripy

Onoff Twin, 1lock-on, 135mm

### amortyzator

Rock Shox Super Deluxe Coil Select R, 225x70mm. LNM ST B1, Linear rebound, Medium compression, spring preload. Trunnion top mount, 30x8mm bottom bushings

**przedni hamulec**

Sram DB8, oversized 4-piston caliper, Centerline 220mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

**tylny hamulec**

Sram DB8, oversized 4-piston caliper, Centerline 203mm IS 6 bolts one-piece rotor, steel-backed metal sintered pads

**regulacja amortyzatora**

Medium compression, linear rebound. Spring rate: S size 400 lbs, M size 400 lbs, L size 450 lbs, XL size 500 lbs

**korba**

34T, steel, X-SYNC

**mocowanie przerzutki**

Mondraker M068

## Galeria

