

# PODIUM CARBON, TRANSLUCENT GREEN CARBON/RACING SILVER, 2023

obj. č: 010.23037

Sugerowana cena

20.999 zł

Aktualna cena

15.599 zł



## Specyfikacje techniczne

|                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                            |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>produkowane rozmiary</b><br>S: 380mm / M: 420mm / L: 470mm / XL: 510mm                                                                                                                                                                                              | <b>rama</b><br>Podium 29 Stealth Air Carbon, XC Forward Geometry, BSA bottom bracket, tapered head tube, HHG internal cable routing, Boost 12x148mm rear axle, dedicated 1X drivetrain design, Flatmount brake compatible, |
| <b>widelec</b><br>Rockshox SID SL Base RL 29, 100mm, Charger, DebonAir, tapered steerer tube, Boost 15x110mm axle, 32mm aluminum stanchions, offset 44mm. Settings: OneLock 2 position remote compression (open/lock), low-speed rebound, air preload, RockShox OneLoc | <b>stery</b><br>Onoff Titan tapered for 1-1/8" to 1-1/2" head tube, ACB sealed bearings, top 41.8x30.5x8x45°x45°, bottom 51.9x40x8x45°x45°                                                                                 |
| <b>przerzutka</b><br>Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1                                                                                                                                                                    | <b>manetki</b><br>Sram Trigger GX Eagle, 12s, X-Actuation 1:1                                                                                                                                                              |
| <b>klamki hamulca</b><br>Sram Level TL, Direct Link actuation, tooled reach adjust, lever pivot bushings                                                                                                                                                               | <b>uchwyty</b><br>Sram GX Eagle, Boost, DUB axle, Direct Mount chain ring, S size: 170mm, M/L/XL size: 175mm                                                                                                               |
| <b>support</b><br>Sram DUB BSA, sealed bearings, 73mm                                                                                                                                                                                                                  | <b>kierownica</b><br>Onoff Sulfur 0.2, double butted 6061 alloy, rise: 4.8mm, width: 760mm, 9° backsweep, 0° upsweep, 31.8mm barbare                                                                                       |
| <b>mostek</b><br>MDK, 6061 T6 Alloy, 31.8mm barbare, rise: +/-5°, length: sizes S/M: 60mm, size L: 70mm, size XL: 80mm                                                                                                                                                 | <b>szttyca</b><br>Onoff Sulfur 0-R, 6061 T6 Alloy, 3D forged, diameter 27.2mm, length 400mm                                                                                                                                |
| <b>siodełko</b><br>Fizik Antares R7                                                                                                                                                                                                                                    | <b>piasta przednia</b><br>Mavic, Boost 15x110mm, IS 6 bolts                                                                                                                                                                |
| <b>tylna piasta</b><br>Mavic, Boost 12x148mm, ID360 Ratchet system, IS 6 bolts, XD freehub                                                                                                                                                                             | <b>łańcuch</b><br>Sram NX Eagle, 12s, Powerlock                                                                                                                                                                            |
| <b>kaseta</b><br>Sram XG-1275, 10-50T, 12s                                                                                                                                                                                                                             | <b>szprychy</b><br>Mavic straight-pull double butted, contactless lacing                                                                                                                                                   |
| <b>rafki</b><br>Mavic Crossmax 29, 25mm internal width, welded rim, hookless, tubeless ready, 24 spokes                                                                                                                                                                | <b>obudowa</b><br>Maxxis Rekon Race 29x2.35, EXO protection, tubeless ready, 120TPI, folding bead                                                                                                                          |
| <b>zamówienie numer</b><br>010.23037                                                                                                                                                                                                                                   | <b>gripy</b><br>Onoff Twin, 1lock-on, 135mm                                                                                                                                                                                |

|                                                                                                                                 |                                                                                                                               |
|---------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| <b>przedni hamulec</b><br>Sram Level TL, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad | <b>tylny hamulec</b><br>Sram Level TL, 2 piece caliper, Centerline 160mm IS 6 bolts one-piece rotor, steel-backed organic pad |
| <b>korba</b><br>34T, CNC-machined alloy, X-SYNC 2                                                                               | <b>mocowanie przerzutki</b><br>Sram UDH                                                                                       |

Galeria

