

# RAZE CARBON R, RACING SILVER/ORANGE, 2023

obj. č: 010.23085



## Specyfikacje techniczne

### produkowane rozmiary

S: 380mm / M: 420mm / L: 450mm / XL: 500mm

### rama

Raze 29 Stealth Air full Carbon, Zero Suspension System, 130mm travel, Forward Geometry, Carbon Monoblock upper link, Boost 12x148mm rear axle, tapered head tube, 73mm BSA bottom bracket, dedicated 1x drivetrain design, HHG internal cable routing, Enduro MAX sealed bearings, shock mudguard, ISCG 05, custom frame protectors.

### widelec

Fox 36 29 Float GRIP EVOL Performance, 150mm, tapered steerer tube, Boost 15x110mm axle, 44mm offset. Settings: 3 positions with micro adjust compression, low-speed rebound, air preload

### stery

Acros custom for 1-1/2

### przerzutka

Sram GX Eagle, Type 3 roller bearing clutch, cage lock, 1x12s, X-Actuation 1:1

### manetki

Sram Trigger NX Eagle, 12s, X-Actuation 1:1

### klamki hamulca

Sram G2, SwingLink, tool-free reach adjust

### uchwyty

Truvativ Stylo 7k Eagle, Boost, DUB axle, Direct mount chain ring, S/M size: 170mm, L/XL size: 175mm

### support

Sram DUB BSA, sealed bearings, 73mm

### kierownica

Onoff Sulfur 1.0 double butted 6061 alloy, rise: 20mm, width: 800mm, 9° backsweep, 5° upsweep, 31.8mm barbore

### mostek

Onoff Sulfur FG 30mm 0°, 6061 forged alloy, 31.8mm barbore

### szttyca

Onoff Pija dropper internal, diameter 31.6mm, S size: 405x95-125mm, M size 458x120-150mm, L size: 498x140-170mm, XL size: 498x140-170mm

### siodełko

Fizik Antares R7

### piasta przednia

Infinity hub, Boost 15x110mm, IS 6 bolts

### tylna piasta

Infinity hub, Boost 15x110mm, IS 6 bolts

### łańcuch

Sram NX Eagle, 12s, Powerlock

### kaseta

Sram XG-1275, 10-52T, 12s

### szprychy

24 straight-pull double butted spokes

### rafki

Sram G2, SwingLink, tool-free reach adjust

### obudowa

Maxxis Dissector 29x2.4 WT, tubeless ready, 3C MAXX TERRA compound, EXO+ protection, 120TPI, folding bead / Maxxis Aggressor 29x2.3, tubeless ready, dual compound, Exo protection, 60TPI, folding bead

### zamówienie numer

010.23085

### gripy

Onoff Desert, 1lock-on, 135mm

**amortyzator**  
Fox Float DPS LV EVOL Performance, 205x57.5mm.  
Settings: rebound, 3-position compression adjustment (Open/Mid/Lock), air preload. Trunnion top mount, 30x8mm bottom bushings

**przedni hamulec**  
Sram G2 R, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

**tylny hamulec**  
Sram G2 R, 4-piston caliper, Centerline 180mm IS 6 bolts one-piece rotor, steel-backed organic pads

**regulacja amortyzatora**  
Light compression, light rebound, air volume spacer 0.6

**korba**  
32T, CNC-machined alloy, X-SYNC 2

**mocowanie przerzutki**  
Sram UDH

Galeria

